



Technical Data	X 120	X 1000 Unidrive	X 1000D Unidrive	X 1740
Speed range [1/min] 230V-Version	10.000 – 33.000	4.000 – 35.000	4.000 – 35.000	2.500 – 23.000
Speed range [1/min] 115V-Version	5.000 – 32.000	4.000 – 35.000	4.000 – 35.000	2.500 – 23.000
Motor power [W]	140	1.050	1.050	1.800
Display	-	-	yes	-
Volume range, max. (H2O) [ml]	1.500	2.000	2.000	20.000
Noise without tool, max [dB]	86	78	78	87
Applicable Dispersing Tools	T 6 T 10 T 17	T 6 T 10 T 17 T 20 / G 20	T 6 T 10 T 17 T 20 / G 20	T 30 / G 30 T 40 / G 40
Power supply [V]	See: order information	See: order information	See: order information	See: order information
Weight [kg]	0.75	2.1	2.1	4.7
Dimensions [L x D mm]	220 x 53	290 x 75	290 x 75	360 x 100
Protection class according to DIN EN 60529	IP20	IP20	IP20	IP20

Order Information	Part Number			
230 VAC / 50Hz, EU plug (Type F)	60404-0000	60402-0050	60406-0050	60408-0000
115 VAC / 60Hz, USA plug (Type B)	60404-0001	60402-0051	60406-0051	60408-0001



Accessories	Part Number	Description
Pedestal stand	60491-0000	Plattform dimensions: 330 x 220 mm. Rod diameter: 16 mm, lenght: 690 mm
Crossover clamp budget	60492-0000	Aluminium white coated clamp. For support rod: 6-12 mm
Crossover clamp standard	60492-0050	Stainless steel clamp. For support rod: 6-12 mm
Crossover clamp with 2 clamp levers	60492-0020	Stainless steel clamp with clamp levers. For support rod: 6-12 mm
Special clamp	60495-0000	Clamp to fix the X 1740 to the stand. For support rod: 12-35 mm
Universal key	60470-0000	Universal rotor wrench for tools T 6 – T 30 / G 30
Socket wrench	60471-0000	Socket wrench for all tools
Rotor wrench T10	60472-0000	Rotor wrench for T 10 only
Rotor wrench T 30	60476-0000	Rotor wrench for T 30 / G 30
Rotor wrench T 40	60477-0000	Rotor wrench for T 40 / G 40