

Order information and accessories.

Authorized extension of your system.

Depending on your specific requirements, it is possible to expand the PT 6100 D drive with our functional accessories. Our expert personnel will be happy to assist you and answer all the questions you might have.

DRIVES

Sales No.	Product	Description
Drive Unit		
11010110	PT 6100 D, 230 V	EU-power cable, PC software, RS-232 /USB connection cable
11010111	PT 6100 D, 230 V	CH-power cable, PC software, RS-232 /USB connection cable
11010112	PT 6100 D, 230 V	UK-power cable, PC software, RS-232 /USB connection cable
11010113	PT 6100 D, 100 – 120 V	Power cable, PC software, RS-232 /USB connection cable
Drive Unit is sold with stand and accessories		
11090090	PT 6100 D, 230 V, Package	Drive Unit. EU-Power cable, stand ST-P 14 /590+500, PC software, RS-232 /USB connection cable
11090091	PT 6100 D, 230 V, Package	Drive Unit. CH-Power cable, stand ST-P 14 /590+500, PC software, RS-232 /USB connection cable
11090092	PT 6100 D, 230 V, Package	Drive Unit. UK-Power cable, stand ST-P 14 /590+500, PC software, RS-232 /USB connection cable
11090093	PT 6100 D, 100-120 V, Package	Drive Unit. UK-Power cable, stand ST-P 14 /590+500, PC software, RS-232 /USB connection cable



ADAPTER



Sales No.	Product	Description
11035001	Adapter PT-DA/PTA (F / A)	This adapter connects older A-coupling dispersing aggregates such as PT-K /PT-G with F-coupling drive units.

TEMPERATURE PROBE



Sales No.	Product	Description
11020050	PT 100 (for POLYTRON® PT 3100 D and PT 6100 D, for measuring the product temperature. The probe can be directly connected to the rear panel of the device).	<ul style="list-style-type: none"> - Temperature range 0 °C to 120 °C - Temperature displayed on LCD display - If the temperature probe is used with the PC software, the temperature is displayed and you can set temperature limits and have the software record the current temperatures.