


Swing Rotor, GRS-B-1000-4

- 4 loadings
- Max. RPM : 3,700
- Angle from axis during rotation : $\angle 90^\circ$
- Rotor dimension / weight ($\varnothing \times L$, mm / g) : 337 x 83 / 5,120
- Supplied with a lubricant



1,000 mL Hi-capacity Bucket,
GLB-h1000-1000

Max. RPM / RCF : 3,700 / 3,092
 Max. Radius (mm) : 202
 Hole dimension (w x d x h, mm) : 110 x 168.7 x 95
 Max. height for tube fit (mm) : 160
 Hole bottom type : Flat

Tube							
Tube capacity (mL)	2.0 ~ 4 mL VT	4 ~ 7 mL VT	8 ~ 10 mL VT	14 mL	15	15 mL conical	50
Tube Dimension ($\Phi \times L$, mm)	13 x 75	13 x 100	16 x 100	15.7 x 96	16 x 120	17 x 120	29 x 108
Adapter							
Cat. No.	GAM-5-48(h1000)	GAM-5-48(h1000)	GAM-10-38(h1000)	GAM-10-38(h1000)	GAM-15-29(h1000)	GAM-c15-29(h1000)	GAM-50-13(h1000)
Rack capacity (ea / 4)	48 / 192	48 / 192	38 / 152	18 / 72	29 / 116	29 / 116	13 / 52
Rack hole dimension ($\Phi \times L$, mm)	13.2 x 50	13.2 x 85	16 x 85	16 x 40	17.2 x 85	17 x 90	29.2 x 87
Rack hole bottom type	Round	Round	Round	Round	Round	Conical	Round
Max. height tube fit (mm)	125	125	125	125	130	130	130
Max. radius (mm)*	192	192	192	192	198	202	198
Max. RCF (g-force)*	2,939	2,939	2,939	2,939	3,030	3,092	3,030

Tube			
Tube capacity (mL)	50 mL conical	50 mL conical (skirted)	250
Tube Dimension ($\Phi \times L$, mm)	29.5 x 118	29.5 x 118	61.5 x 128
Adapter		 with GAS-sc50(c50)	
Cat. No.	GAM-c50-13(h1000)	GAM-c50-13(h1000)	GAM-250-2(h1000)
Rack capacity (ea / 4)	13 / 52	9 / 36	2 / 8
Rack hole dimension ($\Phi \times L$, mm)	29.5 x 92.5	29.5 x 78	62 x 87
Rack hole bottom type	Conical	Flat	Flat
Max. height tube fit (mm)	130	143	155
Max. radius (mm)*	202	184.5	198
Max. RCF (g-force)*	3,092	2,824	3,030