



Fixed Angle Rotor, GRF-B-250-6

- Capacity : 6 x 250 mL plus 6 x 15 mL
- Max. RPM / RCF 8.500 / (9,144; 8,293)
- Hole angle from axis during rotation : $\angle 25^\circ$
- Hole dimension ($\varnothing \times L, \text{mm}$) : 62 x 100 (250 mL) / 17.1 x 94 (15 mL)
- Hole bottom type : Flat (250 mL) / Round (15 mL)
- Max. height for tube fit (mm) : 130 (250 mL) / 120 (15 mL)
- Supplied with a lid with protruding screw for coupling into motor shaft


















Tube		
Tube capacity (mL)	15	250
Tube Dimension ($\Phi \times L, \text{mm}$)	16 x 120	61.5 x 128
Max. radius (mm)	131.3	134
Max. RCF (g-force)	9,395	9,588

Fixed Angle Rotor, GRF-B-85-6

- Capacity : 6 x 85 mL
- Max. RPM / RCF : 12,000 / 16,019
- Hole angle from axis during rotation : $\angle 25^\circ$
- Hole dimension ($\varnothing \times L, \text{mm}$) : 38.5 x 100
- Hole bottom type : Round
- Max. height for tube fit (mm) : 125
- Supplied with a lid with protruding screw for coupling into motor shaft
- Two rubber O-rings inserted



Tube								
Tube capacity (mL)	15	15 mL conical	25 mL conical	25 mL conical	30	50	50 mL conical	85 mL
Tube Dimension ($\Phi \times L, \text{mm}$)	16 x 120	17 x 120	28.8 x 83	28.8 x 78.5	25.7 x 101.4	29 x 108	29.5 x 118	38 x 106
Adapter								None
Cat No.	GAS-15(85)	GAS-c15(85)	GAS-c25(85)	GAS-c25(85)	GAS-30(85)	GAS-50(85)	GAS-c50(85)	-
Adaptor hole dimension ($\Phi \times L, \text{mm}$)	17 x 94	17 x 98	29.5 x 62.5	29.5 x 62.5	26 x 85.4	29 x 95	29.5 x 98	-
Adaptor hole bottom type	Round	Conical	Conical	Conical	Round	Round	Conical	-
Max. radius (mm)*	92.5	90.5	80.9	80.9	92.2	93.5	91.5	99.5
Max. RCF (g-force)*	14,843	14,570	13,024	13,024	14,843	15,053	14,731	16,019