







## Fixed Angle Rotor, GRF-B-m2.0-30

- Capacity : 30 x 1.5/2.0 mL
- Max. RPM / RCF : 16,000 / 27,590
- Hole angle from axis during rotation :  $\angle 45^\circ$
- Hole dimension ( $\varnothing \times L$ , mm) : 11.1 x 39
- Hole bottom type : Round
- Max. height for tube fit (mm) : 52
- Supplied with a lid with protruding screw for coupling into motor shaft
- Two rubber O-rings inserted





Tube				
Tube capacity (mL)	0.2	0.5	1.5/2.0	2.0 mL screw cap
Tube Dimension ( $\Phi \times L$ , mm)	6 x 8	8 x 30	11 x 38	10.1 x 46
Adapter			None	None
Cat No.	GAS-m0.2(2)	GAS-m0.5(2)	-	-
Adaptor hole dimension ( $\Phi \times L$ , mm)	6.5 x 23	8 x 31	-	-
Adaptor hole bottom type	Open	Open	-	-
Max. radius (mm)	79	86	96.4	96.4
Max. RCF (g-force)	22,610	24,614	27,590	27,590

## Fixed Angle Rotor, GRF-B-s0.2-64

- Capacity : 8 x 8-Tube PCR strips, 64 x 0.2 mL
- Max. RPM / RCF : 12,000 / 10,803
- Hole angle from axis during rotation :  $\angle 45^\circ$
- Hole dimension ( $\varnothing \times L$ , mm) : 6.5 x 16
- Hole bottom type : Round
- Max. height for tube fit (mm) : 25
- Supplied with a lid



Tube		
Tube capacity (mL)	0.2	8-Strip tube
Tube Dimension ( $\Phi \times L$ , mm)	6 x 8	6 x 8
Max. radius (mm)	Inner 58.6 Outer 67.1	Inner 58.6 Outer 67.1
Max. RPM	12,000	12,000
Max. RCF (g-force)	Inner 9,434 Outer 10,803	Inner 9,434 Outer 10,803