


Swing Rotor, GRS-B-100-6

- 6 loadings
- Max. RPM : 4,000
- Angle from axis during rotation: $\angle 90^\circ$
- Supplied with a lubricant



Bio-Safe Porton Down Certified



100 mL Bucket with a Cap
GLBB-b100-100

Max. RPM / RCF : 4,200 / 3,424
 Max. Radius (mm) : 173.6
 Hole dimension ($\Phi \times L$, mm) : 47 x 99
 Max. height for tube fit (mm) : 120 (w/ cap) / 130 (w/o cap)
 Hole bottom type : Flat
 Supplied with a cap and O-ring, No cap version is also available

| Tube | | | | | | | | | |
|--|-------------------|-------------------|----------------|----------------|---------------|----------------|-----------------|------------------|---------------|
| Tube capacity (mL) | 1.5 ~ 2.0 | 2.0 mL screw cap | 5 mL conical | 5 mL conical | 2.6 ~ 7 | 4 ~ 10 | 15 | 15 mL conical | 15 mL conical |
| Tube Dimension ($\Phi \times L$, mm) | 11 x 38 | 10.1x46 | 16 x 59 | 16 x 67 | 13 x 75 | 16 x 100 | 16 x 120 | 17 x 120 | 17 x 120 |
| Adapter | | | | | | | | | |
| Cat. No. | GAM-m2.0-6 (b100) | GAM-m2.0-6 (b100) | GAM-c5-3(b100) | GAM-c5-3(b100) | GAM-7-5(b100) | GAM-10-5(b100) | GAM-15-3 (b100) | GAM-c15-3 (b100) | GAS-c15(b100) |
| Rack capacity (ea / 4) | 6 / 36 | 6 / 36 | 3 / 18 | 3 / 18 | 5 / 30 | 5 / 30 | 3 / 18 | 3 / 18 | 1 / 6 |
| Rack hole dimension ($\Phi \times L$,mm) | 11 x 39 | 11 x 39 | 17.2 x 52 | 17.2 x 52 | 13.5 x 60 | 16 x 60 | 17.5 x 105 | 17.2 x 106.5 | 17.2 x 106.5 |
| Rack hole bottom type | Round | Round | Conical | Conical | Round | Flat | Flat | Conical | Conical |
| Max. height tube fit (mm) | 115 | 115 | 75 | 75 | 115 | 115 | 120 | 120 | 120 |
| Max. radius (mm)* | 168.6 | 168.6 | 110.1 | 110.1 | 168.6 | 168.6 | 170.6 | 173.6 | 173.6 |
| Max. RCF (g-force)* | 3,325 | 3,325 | 2,171 | 2,171 | 3,325 | 3,325 | 3,364 | 3,424 | 3,424 |

| Tube | | | | | | | | |
|--|---------------|---------------|--------------|--------------|---------------|-------------------------|--------------|---------------|
| Tube capacity (mL) | 25 mL conical | 25 mL conical | 30 | 50 | 50 mL conical | 50 mL conical (Skirted) | 85 | 100 |
| Tube Dimension ($\Phi \times L$, mm) | 28.8 x 83 | 28.8 x 78.5 | 25.7 x 101.4 | 29 x 108 | 29.5 x 118 | 29.5 x 118 | 38 x 106 | 44 x 115 |
| Adapter | | | | | | | | |
| Cat. No. | GAS-c25(b100) | GAS-c25(b100) | GAS-30(b100) | GAS-50(b100) | GAS-c50(b100) | GAS-sc50(b100) | GAS-85(b100) | GAS-100(b100) |
| Rack capacity (ea / 4) | 1 / 6 | 1 / 6 | 1 / 6 | 1 / 6 | 1 / 6 | 1 / 6 | 1 / 6 | 1 / 6 |
| Rack hole dimension ($\Phi \times L$,mm) | 17.2 x 52 | 17.2 x 52 | 26 x 86 | 29.5 x 95.9 | 30 x 100 | 29.8x100 | 38.5 x 96.4 | 44.2 x 93 |
| Rack hole bottom type | Conical | Conical | Round | Round | Conical | Flat | Round | Round |
| Max. height tube fit (mm) | 118 | 118 | 118 | 118 | 120 | 120 | 118 | 118 |
| Max. radius (mm)* | 172.1 | 172.1 | 172.1 | 171.6 | 171.6 | 171.6 | 172.1 | 168.6 |
| Max. RCF (g-force)* | 3,394 | 3,394 | 3,394 | 3,384 | 3,384 | 3,384 | 3,394 | 3,325 |