

PERFECTION IS AN UNDERSTATEMENT



(+

Ξ

iStir OH Elite Elite Series Of Overhead Stirrers

While the market is saturated with overhead stirrers, most of them fall short when it comes matching customer's expectations in terms of performance and durability. As soon as these devices encounter high-viscosity or large quantities of solutions, they falter in terms of performance which restricts the users in terms of the work that can be done with these devices. Even maintenance is also a frequent issue with such devices as they frequently break down or have to undergo frequent maintenance which puts a big question on their durability.

Neuation is markedly different when it comes to our approach to designing and developing overhead stirrers Guided by a dedicated R&D department engaged in constant research about customer needs and user-experience, we were able to design and develop our excellent range of iStir Elite stirrers. Featuring intelligent design and high-performance components, these devices come with unique features such as built-in overload, overcurrent and over-temperature safety, Power Intermittent mode and counter speed control to meet even the most demanding stirring requirements.

Product Features



Brushless DC motor delivers ultra quiet performance and a maintenance-free long life.



Microprocessor controlled for efficient performance even under high load. Volume Range Upto 100L



Viscosity Upto 70,000 mpas



Variable stirring speed settings upto 2000 RPM for powerful performance

> Smart Control Stirring feature to ensure constant stirring change even in viscosity





Variable timer setting ranging from 1 minute to 99 hours 59 mins as well as an Infinite mode

CW & CCW motion for efficient & thorough mixing.





Powerful motor delivers torque upto 100 Ncm to stir solutions with viscosity up to 70,000 mPas & 100 L volume

Product Features



Large and clear display enables easy viewing of all critical parameters



Built-in overload, overcurrent and overtemperature safety feature to ensure complete safety

Ð

In case of power failure, the Power Intermittent mode starts the device automatically as soon as power is restored and runs for the remaining left time Safe Low Voltage Device



IP42 class compliant rating for unmatched durability



Small footprint saves valuable bench space









Wide-variety of impellers available to suit all stirring needs

Specifications

iStir OH 50 Elite			
Motor Type	Brushless DC		
Capacity (H20)	50 Liters		
Speed Range	60 - 2000 RPM		
Torque	50 Ncm		
Viscocity	30000 mPas		
Timer	1 min to 99 hr 59 mins & infinity mode		
Direction of Rotation	Reversible - CW/CCW		
Protection Class	IP 42		
Dimension (Head)	102x 249 x 242mm		
Weight	5.1 kgs		

iStir OH 75 Elite			
Motor Type	Brushless DC		
Capacity (H20)	75 Liters		
Speed Range	60 - 2000 RPM		
Torque	75 Ncm		
Viscocity	50000 mPas		
Timer	1 min to 99 hr 59 mins & infinity mode		
Direction of Rotation	Reversible - CW/CCW		
Protection Class	IP 42		
Dimension (Head)	102x 249 x 242mm		
Weight	5.1 kgs		

iStir OH 100 Elite				
Motor Type	Brushless DC			
Capacity (H20)	100 Liters			
Speed Range	60 - 1300 RPM			
Torque	100 Ncm			
Viscocity	70000 mPas			
Timer	1 min to 99 hr 59 mins & infinity mode			
Direction of Rotation	Reversible - CW/CCW			
Protection Class	IP 42			
Dimension (Head)	102x 249 x 242mm			
Weight	5.1 kgs			

Ordering Information

iStir OH Elite			
Product Name Cat #			
iStir OH 50 Elite	OHS2 - 1101-EU/UK/AU/US		
iStir OH 75 Elite	OHS2 - 1201-EU/UK/AU/US		
iStir OH 100 Elite	OHS2 - 1301-EU/UK/AU/US		

Accessories				
Product Name H-stand Cat. No. # OHS1-HS Product Name Boss Head Cat. No. # OHS1-HBH				
Impeller	Dimensions	Blade Type		
OHS2-A01	550 (Blade 50x8)	Propeller Blade		
OHS2-A02	550 (Blade 100x15)	Propeller Blade		
OHS2-A03	800 (Blade 130x15)	Propeller Blade		
OHS2-R01	550 (Blade 50x12)	Cross-welded		
OHS2-R02	550 (Blade 35x12)	Straight Blade		
OHS2-R03	550 (Blade 50x12)	Straight Blade		
OHS2-R05	550 (Blade 60x15)	Pivoting Blade		
OHS2-R07	550 (Blade 80x10)	Collapsible Blade		
OHS2-T02	550 (Blade 38x38)	Square Blade		
OHS2-T03	800 (Blade 70x70)	Square Blade		
OHS2-T05	550 (Blade 45x45)	Anchor Blade	el.	
OHS2-T06	800 (Blade 90x80)	Anchor Blade		
OHS2-T08	550 (Blade 70x70)	Paddle Blade		
OHS2-T09	800 (Blade 70x70)	Paddle Blade		
OHS2-T10	550 (Blade 70x80)	Paddle Blade	h	
OHS2-T11	800 (Blade 70x80)	Paddle Blade	(A)	

Accessories			
Cat #	Product Name	Details	
OHS-C1	Key Chuck		
OHS-C2	Keyless Chuck	Ű	
OHS-C3	Collet Chuck		
OHS-CC	Chuck Cover	Ų	



www.neuation.com

AN ISO 9001 : 2015 & ISO 13485 : 2016 CERTIFIED MFG. COMPANY

*We also execute OEM projects. Specifications can be changed without notice for quality improvement.