

HWLAB[®] Micropipette U model

Adjustable-volume pipette



Description

HWLAB[®] pipette U model is designed and manufactured to provide you with a range of robust, accurate and precise pipettes. The HWLAB[®] pipette U model is a fully adjustable, air-displacement pipette with the selected volume shown on a digital indicator (volume display).

Product features

- 3 digits
- Magnifying shape
- Chemical resistance
- 121°C sterilization
- Very low operating force
- Colour indicates pipette volume
- Positioned for perfect ergonomics
- Only a few turns to reach your desired volume

Ordering information: HWLAB[®] Micropipette U Single channel, adjustable-volume

Cat.No	Model	Volume range	Accuracy	Repeatability
L-2081	U2	0.1-2µl	± 12.0-1.5%	≤6.00-0.70%
L-2082	U10	0.5-10µl	± 2.5-1.0%	≤1.50-0.40%
L-2083	U20	2-20µl	± 2.5-1.0%	≤1.50-0.30%
L-2084	U50	5-50µl	± 2.0-1.0%	≤1.50-0.25%
L-2085	U100	10-100µl	± 1.8-0.8%	≤0.50-0.15%
L-2086	U200	20-200µl	± 1.8-0.6%	≤0.50-0.15%
L-2087	U1000	100-1000 µl	± 1.5-0.6%	≤0.30-0.15%
L-2088	U5000	500-5000 µl	± 1.2-0.6%	≤0.30-0.15%
L-2089	U10ml	1-10ml	± 2.5-0.6%	≤0.30-0.15%

Remark

Quantity per carton: 20 pcs
G.W.: 7.0kg
Dimension: 43x31x27cm